Vol. 46, 1976

# REVIEW OF PHYSICAL CHEMISTRY OF JAPAN

Founded in 1926

#### CONTENTS

Noriyuki Sotani: ESR Studies of the Hexagonal Hydrate of Molybdenum Oxide and Its Changes on Treatments in Vacuo and in Hydrogen	1
Norlyuki Sotani: The Reaction between Thiophene and Hydrogen on the Hexagonal Hydrate of Molybdenum Oxide	9
Etsuko Inada: The Pressure and Temperature Effects on the Walden Products of Na <sup>+</sup> , K <sup>+</sup> , Cs <sup>+</sup> and I <sup>-</sup> in Water	19
Kiyoshi Shimizu, Noriaki Tsuchihashi and Yoshio Furumi: Effect of Pressure on Dissociation of Nickel Sulfate Ion Pair	30
Koichi Watanabe, Masahiko Uematsu and Shogo Saegusa: Thermodynamic  Properties of Gaseous Propane and Propene	39
Erratum: T. Makita, Y. Tanaka and A. Nagashima, Rev. Phys. Chem. Japan, 44, 98 (1974)	54
Erratum: M. Nakahara and I Osugi Rev Phys Chem Japan 45 60 (1075)	56

## THE REVIEW OF PHYSICAL CHEMISTRY OF JAPAN

#### (Butsuri-Kagaku no Shinpo)

Found in 1926

President: Wasaburo Jono Members of Council:

Michio Okamoto (Chief)

Jiro Osugi

Ryozo Goto

Renpei Goto

Eiji Suito

Hiroyuki Hatano

#### Board of Editors:

J. Osugi (Chief)

Kyoto University

R. Goto (Associate) Kyoto Sangyo University

E. Suito (

) Osaka Institute of Technology

S. Shida

Yokohama Univeristy

H. Teranishi

Kyoto Technical University

K. Suzuki

Ritsumeikan University

K. Kuwata

University of Osaka

S. Seki

University of Osaka

R. Fujishiro

T. Hayakawa

Osaka City University

Prefectural University of Osaka

Y. Kubokawa

Prefectural University of Osaka

S. Tsuchihashi

Kobe University

T. Makita

Kobe University

S. Hasegawa

Okayama University

K. Shimizu

Doshisha University

H. Togawa

Doshisha University

#### Secretary:

M. Sasaki

K. Hara

M. Nakahara

S. Fukase

#### June 30, 1976

Communications to the Editor should be addressed to Board of Editors, The Physico-Chemical Society of Japan, Faculty of Science, Kyoto University, Kyoto, Japan.

Business Correspondences should be addressed to: Secretary, The Physico-Chemical Society of Japan, Faculty of Science, Kyoto University, Kyoto, Japan.

Purchase Order should be addressed to: Maruzen Co., Ltd., Nihonbashi, Chuo-ku, Tokyo, Japan.

#### Published by

#### THE PHYSICO-CHEMICAL SOCIETY OF JAPAN

(Nippon Butsuri-Kagaku Kenkyu Kai)

Faculty of Science, Kyoto University, Kyoto, Japan

Printed by KAWAKITA PRINTING CO., LTD., Kyoto, Japan



## Oil and fashion: they're closer than you think

Tellin made industrial history with its now internationally known nolvester thre—Tellin Teloron

polyester fibre—Teijin Tetoron. In fact, Teijin's synthetic fibre technology is so well-known in Asia:that there are several jointcapital plants in full operation throughout the the area.

And, in order to integrate its operations completely, Teijin has already begun to explore oil



resources which are fundamental to the production of synthetic fibres. That's why people call us the "pioneering corporation", in everything from oil to fashion.

Integrated manufacture from Taw materials to finished fabrics.





Set to go on-stream in mid-1969, MITSUI TOATSU's new facility in Osaka will be the largest single-train urea plant ever built. It employs the latest MITSUI TOATSU Urea Process—the Total Recycle C-Improved Process.

MITSUI TOATSU Urea Processes are now in use in 37 plants in 19 countries, with an additional 12 more plants now under construction. World-wide, the production capacity of these plants is reaching to some 8.2 million tons of urea annually—one third of the world's urea capacity.

On October 1st, 1968, Toyo Koatsu merged with Mitsui Chemicals and changed its name to MITSUI TOATSU CHEMICALS, INC.



#### HORIBA, Ltd. offers special application of

Recommendation for application is also a part of our service.

#### Ge(Li)γRay Detector



A coaxial type semiconductor detector made from a lithium-drifted Germanium single crystal. Ideally suitable for precision analysis of  $\gamma$  ray spectrum for its superb energy resolution.

- Energy Resolution: 1.9~1.6 keV
- Ambient radioactivity monitoring.
- Radiochemistry analysis.
- γ ray measurements in nuclear medicine.

units having surface barrier type silicone (semi-conductor) as elements ideally suitable for the measurements of alpha particles, fission fragments or heavy ions. Their measurable energy ranges are, approx. 9.5 MeV with an effective thickness of 60µ for alpha particles and approx. 15 MeV with 120µ, having resolutions ranging from 30 keV to 90 keV.

A spectrum of natural radioactivity in indoor atmosphere measured by Ge (Li) gamma ray detector.

Duration of Measurement: 100,000 sec. Counts Bias Voltage: +2,400v (Numerals at the peaks indicate gamma ray energy(keV).) 2128

GL C92H (equivalent to 50cc)

HORIELA


Si(Li)XRay Detector

This is a semi-conductor radiation detector made from lithium-drifted silicone single crystal, and because of its highest grade resolution expectable from an energy dispersion X ray detector, a simultaneous measurements of multiple elements is possible. It has a wide range of applications such as element analysis of pollutants like suspending 900 1000 1100 1200 1300 dust in atmosphere, X ray micro-analysis or X ray diffraction.

## Channel Numbers (Energies)

#### Silicone Detector Unit for Radiation

Semi-conductor detector





#### Nal(TI) Scintillators for Radiation Measurement

These are the radiation detectors resorting to the phenomenon of a transparent single crystal to scintillate by the incident radiation. They are used for a general counting of gamma rays or soft X rays or for scintillation spectrometer. For meeting different applications, they are made to a variety of types such as standard type, well type, soft X ray type, union type, differential type, side-hole type or scinti-camera type.

### HORIBA, Ltd. HORIBA

Miyanohigashi, Kisshoin, Minami-ku, Kyoto, Japan

Tel: 075-313-8121 Cable: HORIBA KYOTO Telex: 5422130